NSN 3020-00-051-5469



Spur Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-051-5469

Body Style:
Plain, solid

Attachment Method:
Mounting hole
Pitch Diameter:
0.5000 inches

Teeth Quantity:
32

Bore Style:
Plain both ends

Backlash Designation:
Grade c

Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

Mounting Hole Thready Qty Per Inch (tpi):

56 transversely through hub, first end

Mounting Hole Thread Size:

0.086 inches transversely through hub, first end

Mounting Hole Type And Quantity:

1 threaded transversely through hub, first end

Outside Diameter:

0.531 inches

Nominallength:

0.375 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.250 inches first end

Face Width:

0.125 inches

Bore Diameter:

0.188 inches both ends

Hub Style Designator:

Pinned first end

Hub Diameter:

0.375 inches first end

Precision Classification:

Quality number 10 or quality number 11

Material:

Steel comp 416

NSN 3020-00-051-5469 Spur Gear - Page 2 of 2

Fiig: A27300



Material Specification:
Qq-s-764, type 416 cond a federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No