## NSN 3020-00-052-5434



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-052-5434 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 1.6657 inches and 1.6667 inches **Teeth Quantity:** 80 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.707 inches Nominallength: 0.315 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.222 inches first end **Face Width:** 0.093 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.435 inches first end Material: Aluminum alloy 6061 **Material Specification:** 

Qq-a-225/8, t6 federal specification single material response **Surface Treatment:** Anodize

## NSN 3020-00-052-5434

Spur Gear - Page 2 of 2



Ctv/la	n Da	eian	ator:
OLYN	- 00	əiyii	atoi.

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300