## NSN 3020-00-053-3133

Spur Gear - Page 1 of 2





## **Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** Between 1.7212 inches and 1.7222 inches **Teeth Quantity:** 62 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 20 transversely through hub, first end Mounting Hole Thread Size: 0.112 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 1.777 inches Nominallength: 0.295 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.202 inches first end Face Width: 0.093 inches **Bore Diameter:** 0.187 inches both ends Hub Style Designator: Plain first end **Hub Diameter:** 0.375 inches first end Material: Aluminum alloy 6061 **Material Specification:** Qq-a-225/8, t6 federal specification single material response Style Designator:

Protruding hub

## NSN 3020-00-053-3133

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

