## NSN 3020-00-057-8667

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-057-8667 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.2500 inches **Teeth Quantity:** 120 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.269 inches Nominallength: 0.276 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.187 inches first end **Face Width:** 0.094 inches **Hub Diameter:** 0.370 inches first end **Precision Classification:** Quality number 12 **Special Features:** Alignment hole on 0.5000 bolt circle diameter located on faceof gear Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response **Surface Treatment:** Anodize

### **Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

#### **Style Designator:**

Protruding hub

# NSN 3020-00-057-8667

Spur Gear - Page 2 of 2



| N/a               |
|-------------------|
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
|                   |
| Fiig:             |

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: