## NSN 3020-00-057-8781

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-057-8781 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.5625 inches **Teeth Quantity:** 150 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.581 inches Nominallength: 0.276 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end **Face Width:** 0.094 inches **Bore Diameter:** 0.188 inches both ends **Hub Diameter:** 0.370 inches first end **Precision Classification:** Quality number 10 or quality number 11 **Special Features:** Alignment hole located on face of gear, with bolt circlediameter of 0.6250 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response

**Surface Treatment: Surface Treatment Specification:** 

Anodize

Mil-a-8625, type 1 military specification single treatment response

## NSN 3020-00-057-8781

Spur Gear - Page 2 of 2



| Style Designator:     |
|-----------------------|
| Protruding hub        |
| Shelf Life:           |
| N/a                   |
| Unit Of Measure:      |
|                       |
|                       |
| <br>Demilitarization: |
|                       |
| Demilitarization:     |

Mil-std (military Standard):

Mil-a-8625 spec.