## NSN 3020-00-063-8857

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-063-8857

| View Online at https://aerobasegroup.com/nsn/3020-00-063-8857       |
|---|
| Body Style:   |
| Plain, solid  |
| Attachment Method:  |
| Mounting hole   |
| Pitch Diameter:   |
| 1.2500 inches   |
| Teeth Quantity:   |
| 90  |
| Mounting Hole Thread Series Designator:                             |
| Unc transversely through hub, first end                             |
| Mounting Hole Thready Qty Per Inch (tpi):                           |
| 40 transversely through hub, first end                              |
| Mounting Hole Type And Quantity:                                    |
| 1 threaded transversely through hub, first end                      |
| Nominallength:  |
| 0.281 inches  |
| Tooth Form:   |
| Standard  |
| Pressure Angle:   |
| 20.0000 degrees   |
| Distance Between Body Face And Protruding Hub End:                  |
| 0.188 inches first end  |
| Face Width:   |
| 0.093 inches  |
| Bore Diameter:  |
| 0.187 inches both ends  |
| Hub Diameter:   |
| 0.312 inches first end  |
| Precision Classification:   |
| Quality number 13 or quality number 14                              |
| Material:   |
| Aluminum alloy 2024   |
| Material Specification:   |
| Qq-a-225/6, t4 federal specification single material response       |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:                                    |
| Mil-a-8625, type 2 military specification single treatment response |
| Style Designator:   |
| Protruding hub  |
| Shelf Life:   |
| N/a   |

## NSN 3020-00-063-8857

Spur Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.

