NSN 3020-00-063-8863

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-063-8863

Body Style: Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 2.0000 inches **Teeth Quantity:** 192 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.020 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.235 inches first end **Face Width:** 0.093 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** 1 step first end **End Length:** 0.189 inches first end **Precision Classification:** Quality number 10 or quality number 11 **End Diameter:** 0.375 inches first end First Step Length: 0.046 inches first end First Step Diameter:

Material:

Steel comp 416 hub

0.438 inches first end

NSN 3020-00-063-8863

Spur Gear - Page 2 of 2



Material	Specification:	
----------	----------------	--

Qq-s-764, cond a-canceled federal specification single material response hub

Surface Treatment:

Passivate hub

Surface Treatment Specification:

Mil-a-8625, type2 military specification single treatment response body

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.