## NSN 3020-00-063-8893

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-063-8893

Body Style:
Plain, with lightening holes
Attachment Method:
Mounting hole
Pitch Diameter:
2.5000 inches
Teeth Quantity:
180
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 axially through body, first end
Nominallength:
0.375 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.126 inches
Bore Diameter:
0.250 inches both ends
Hub Diameter:
0.500 inches first end
Precision Classification:
Quality number 13 or quality number 14
Mounting Hole Diameter:
0.062 inches transversely through hub, first end
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response body
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 3020-00-063-8893

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.