## NSN 3020-00-068-3805

Spur Gear - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/3020-00-068-3805

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.4792 inches
Teeth Quantity:
46
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
0.498 inches
Nominallength:
0.243 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.153 inches first end
Face Width:
0.089 inches
Bore Diameter:
0.125 inches both ends
0.125 inches both ends  Hub Style Designator:
Hub Style Designator:
Hub Style Designator: Pinned first end
Hub Style Designator: Pinned first end Hub Diameter:
Hub Style Designator: Pinned first end Hub Diameter: 0.295 inches first end

Surface Treatment Specification:

Passivate

Mil-std-171, finish no. 5.4.1 military standard single treatment response

## NSN 3020-00-068-3805

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Demilitarization:

Mil-std (military Standard):

Mil-std-171 spec.