## NSN 3020-00-070-2152

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-070-2152

| Body Style:                                                                 |
|-----------------------------------------------------------------------------|
| Webbed, solid                                                               |
| Attachment Method:                                                          |
| Mounting hole                                                               |
| Pitch Diameter:                                                             |
| 6.0000 inches                                                               |
| Teeth Quantity:                                                             |
| 60                                                                          |
| Bore Style:                                                                 |
| W/counterbore counterbore, first end                                        |
| Hardness Rating:                                                            |
| 30.0 rockwell c and 34.0 rockwell c                                         |
| Mounting Hole Type And Quantity:                                            |
| 8 plain axially through flange and 8 plain axially through flange           |
| Outside Diameter:                                                           |
| 6.198 inches                                                                |
| Tooth Form:                                                                 |
| Standard                                                                    |
| Pressure Angle:                                                             |
| 20.0000 degrees                                                             |
| Distance Between Body Face And Protruding Hub End:                          |
| 0.104 inches first end                                                      |
| Body Recess Depth:                                                          |
| 0.092 inches second end                                                     |
| Face Width:                                                                 |
| 0.438 inches                                                                |
| Bore Diameter:                                                              |
| 3.688 inches counterbore, first end                                         |
| Counterbore Depth:                                                          |
| 0.260 inches counterbore, first end                                         |
| Counterbore Diameter:                                                       |
| 4.748 inches counterbore, first end                                         |
| Hub Style Designator:                                                       |
| Plain first end                                                             |
| Hub Diameter:                                                               |
| 4.938 inches first end                                                      |
| Precision Classification:                                                   |
| Quality number 10                                                           |
| Mounting Hole Diameter:                                                     |
| 0.171 inches axially through flange and 0.279 inches axially through flange |
| Material:                                                                   |
| Steel comp 4340                                                             |

## NSN 3020-00-070-2152

Spur Gear - Page 2 of 2



| Material Specification: |  |
|-------------------------|--|
|                         |  |

Fed standard 66 federal standard single material response

**Surface Treatment:** 

Tin and cadmium

**Style Designator:** 

Protruding hub, recessed body

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A27300