NSN 3020-00-071-3704

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-071-3704

Body Style:
Plain, solid
Attachment Method:
Slot
Pitch Diameter:
0.4688 inches
Teeth Quantity:
30
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
0.499 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.281 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.249 inches first end
Clamping Surface Length:
0.250 inches first end
Precision Classification:
Quality number 10
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response

Protruding hub

Style Designator:

NSN 3020-00-071-3704

Spur Gear - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.