NSN 3020-00-072-7122

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-072-7122

| Body Style: |
|--|
| Webbed, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.6870 inches |
| Teeth Quantity: |
| 19 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Type And Quantity: |
| 2 plain transversely through hub, first end |
| Outside Diameter: |
| 1.781 inches |
| Nominallength: |
| 1.300 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.650 inches first end |
| Face Width: |
| 0.075 inches |
| Bore Diameter: |
| 0.250 inches both ends |
| Hub Style Designator: |
| 2 steps both ends |
| End Length: |
| 0.140 inches second end |
| End Diameter: |
| 0.187 inches both ends |
| First Step Length: |
| 0.320 inches first end |
| First Step Diameter: |
| 0.438 inches second end |
| Second Step Length: |
| 0.160 inches first end |
| Second Step Diameter: |
| 0.250 inches both ends |
| Mounting Hole Diameter: |
| 0.600 inches transversely through hub, first end |

NSN 3020-00-072-7122

Spur Gear - Page 2 of 2



| Material: |
|---|
| Steel comp 303 |
| Material Specification: |
| Mil-s-7720, comp 303s military specification single material response |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

Mil-s-7720 spec.

Mil-std (military Standard):

A27300