NSN 3020-00-074-3995

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-074-3995

| Body Style: |
|--|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.2370 inches |
| Teeth Quantity: |
| 99 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Thread Series Designator: |
| Unc transversely through hub, first end |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 40 transversely through hub, first end |
| Mounting Hole Thread Size: |
| 0.112 inches transversely through hub, first end |
| Mounting Hole Type And Quantity: |
| 1 threaded transversely through hub, first end |
| Outside Diameter: |
| 1.262 inches |
| Nominallength: |
| 0.375 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.250 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.125 inches both ends |
| Hub Style Designator: |
| Pinned first end |
| Hub Diameter: |
| 0.375 inches first end |
| Material: |
| Steel comp 303 hub |
| Material Specification: |
| Qq-a-225/6, t351 federal specification single material response body |
| Style Designator: |
| Protruding hub |
| |

NSN 3020-00-074-3995

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.

