NSN 3020-00-074-6776

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-074-6776 **Attachment Method:** Mounting hole **Pitch Diameter:** Between 1.2493 inches and 1.2500 inches **Teeth Quantity:** 80 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.281 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.281 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.310 inches first end Material: Steel comp 303 hub **Material Specification:** Qq-s-763, class 303, cond a federal specification single material response hub **Surface Treatment:** Anodize body and passivate body **Style Designator:** Protruding hub Shelf Life:

N/a

NSN 3020-00-074-6776

Spur Antibacklash Gear - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300