## NSN 3020-00-074-9355



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-074-9355 **Body Style:** Webbed, with lightening holes **Spline Quantity:** 20 first end Pitch Diameter: 3.0000 inches **Teeth Quantity:** 60 **Bore Style:** W/counterbore second end **Spline Pitch Diameter:** 0.8333 inches first end **Backlash Designation:** Grade c Hardness Rating: 42.0 rockwell c and 45.0 rockwell c **Outside Diameter: 3.100** inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.359 inches first end **Face Width:** 0.437 inches **Bore Diameter:** 0.791 inches both ends **Counterbore Depth:** 0.100 inches second end **Counterbore Diameter:** 1.008 inches second end **Hub Style Designator:** Plain both ends **Hub Diameter:** 1.258 inches second end **Precision Classification:** 

Precision Classification
Quality number 9

Material:
Steel

Surface Treatment:
Phosphate

## NSN 3020-00-074-9355

Spur Gear - Page 2 of 2



•	_			
Style	1)6	SIU	na	t∩r∙
Otylo		JIG	ııu	w.

Protruding hubs

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300