## NSN 3020-00-077-0579

Spur Gear-slip Clutch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-077-0579 **Attachment Method:** Mounting hole Pitch Diameter: 1.2500 inches **Torque Capacity:** 16.00 inch-ounces **Teeth Quantity:** 80 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 plain transversely through hub, first end and 1 threaded transversely through hub, first end **Outside Diameter:** 1.2813 inches Nominallength: 0.562 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.219 inches both ends **Face Width:** 0.125 inches **Bore Diameter:** 0.187 inches both ends Distance Between Face Edge And Body End: 0.218 inches **Hub Style Designator:** Plain first end **Hub Diameter:** 0.500 inches first end **Precision Classification:** Quality number 10 or quality number 11 **Mounting Hole Diameter:** 

Material:

Steel comp 303 hub

0.047 inches transversely through hub, first end

## NSN 3020-00-077-0579

Spur Gear-slip Clutch - Page 2 of 2



Material Specification
------------------------

Mil-s-7720 military specification single material response hub

**Surface Treatment:** 

Passivate hub

**Style Designator:** 

Adjustable torque, coil spring loaded

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-b-5687 spec.