NSN 3020-00-079-7122

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-079-7122

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
2.5000 inches
Teeth Quantity:
160
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 transversely through hub, first end
Hardness Rating:
235.0 brinell standard hub
Mounting Hole Thread Size:
0.138 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
2.531 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.265 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.188 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.219 inches first end
Precision Classification:
Quality number 10 or quality number 11
End Diameter:

0.375 inches first end

NSN 3020-00-079-7122

Spur Gear - Page 2 of 2



First Step Length:
0.046 inches first end
First Step Diameter:
0.438 inches first end
Material:
Steel comp 416 hub
Material Specification:
Qq-s-763, cl 416 federal specification single material response hub
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Mil-s-5002 federal specification 1st treatment response hub
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-a-8625 spec.