## NSN 3020-00-080-6564

Groove Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-080-6564 **Counterbore Depth:** 0.120 inches **Groove Depth:** 0.470 inches **Groove Width:** 0.375 inches **Outside Diameter:** 5.600 inches **Overall Length:** 2.660 inches **Keyway Width:** Between 0.188 inches and 0.190 inches **Bore Diameter:** 1.188 inches **Bore Length:** 0.840 inches **Distance From Center Of Bore To Bottom Of Keyway:** Between 0.686 inches and 0.691 inches V Groove Angle In Deg: 37.0 Pitch Diameter: 5.250 inches **Material And Location:** Iron, cast **Face Width:** 1.140 inches **Design Form:** Webbed **Bore Type:** Straight Bearings: Not included **Groove Quantity:** 2 **Counterbore Feature:** Not included **Keying Facility:** Included **Keying Facility Type:** 

Keyway

**Split Hub Feature:** 

Not included

## **NSN 3020-00-080-6564** Groove Pulley - Page 2 of 2



Neb/spoke Relationship To Face Centerline:
Offset
Lightening Hole:
Not included
ntegral Cooling Vane:
Not included
Groove Shape:
V
Standard V-belt Section Designation For Which Designed:
31
Bore Feature:
ncluded
Protruding Hub Characteristic:
Plain
Hub End Outside Diameter And Location:
1.620 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
1.520 inches aa end and 1.820 inches bb end
Special Features:
Aa end has heavy 7.378 in.Dia integral flange for balancing purposes
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
Г353-а