## NSN 3020-00-080-6578

Spur Gear - Page 1 of 2



#### **Body Style:**

Plain, solid

#### **Attachment Method:**

Clamp

## **Pitch Diameter:**

Between 1.9990 inches and 2.0000 inches

## **Teeth Quantity:**

160

Bore Style:

Plain both ends

**Outside Diameter:** 

### 2.024 inches

Tooth Form:

#### Standard

Pressure Angle:

#### 20.0000 degrees

#### Distance Between Body Face And Protruding Hub End:

0.281 inches first end

#### Face Width:

0.125 inches

## Bore Diameter:

0.120 inches both ends

## Hub Style Designator:

Split first end

#### Hub Diameter:

0.187 inches first end

#### **Clamping Surface Length:**

0.250 inches first end

#### **Precision Classification:**

Quality number 10

#### Material:

Steel comp 303

#### Material Specification:

Qq-s-764, type 303 federal specification single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35, type 2 federal specification single treatment response

## Style Designator:

Protruding hub

## Shelf Life:

N/a



# NSN 3020-00-080-6578

Spur Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

