NSN 3020-00-086-4589

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-086-4589

| Attachment Method: |
|---|
| Mounting hole |
| Pitch Diameter: |
| 3.2812 inches |
| Teeth Quantity: |
| 105 |
| Bore Style: |
| W/counterbore both ends |
| Mounting Hole Thread Series Designator: |
| Unc axially through hub, first end |
| Mounting Hole Thready Qty Per Inch (tpi): |
| |
| 56 axially through hub, first end |
| Mounting Hole Type And Quantity: |
| 3 threaded axially through hub, first end |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Face Width: |
| 0.150 inches |
| Bore Diameter: |
| 0.241 inches both ends |
| First Step Diameter: |
| 1.250 inches first end |
| Bolt Hole Circle Diameter: |
| 0.906 inches axially through hub, first end |
| Material: |
| Aluminum alloy 6061 |
| Material Specification: |
| Qq-a-225/8, t6 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 military specification single treatment response |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 3020-00-086-4589

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.