# NSN 3020-00-086-4589

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-086-4589

Attachment Method:

Mounting hole

Pitch Diameter:

3.2812 inches

## Teeth Quantity:

105

Bore Style:

W/counterbore both ends

#### Mounting Hole Thread Series Designator:

Unc axially through hub, first end

#### Mounting Hole Thready Qty Per Inch (tpi):

56 axially through hub, first end

### Mounting Hole Type And Quantity:

3 threaded axially through hub, first end

Tooth Form:

### Standard

**Pressure Angle:** 

20.0000 degrees

#### Face Width:

0.150 inches

### Bore Diameter:

0.241 inches both ends

#### First Step Diameter:

1.250 inches first end

## **Bolt Hole Circle Diameter:**

0.906 inches axially through hub, first end

Material:

Aluminum alloy 6061

#### **Material Specification:**

Qq-a-225/8, t6 federal specification single material response

#### Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

## Style Designator:

Protruding hubs

Shelf Life:

N/a

## Unit Of Measure:

--

### Demilitarization:

No

# NSN 3020-00-086-4589

Spur Gear - Page 2 of 2

Fiig: A27300 Mil-std (military Standard):

Mil-a-8625 spec.

