## NSN 3020-00-087-9733

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-087-9733 **Attachment Method:** Mounting hole Pitch Diameter: 2.5000 inches **Teeth Quantity:** 120 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.113 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 2.5417 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.563 inches first end **Precision Classification:** Quality number 10 Material:

Steel comp 303 hub **Material Specification:** 

Qq-a-225/6 federal specification single material response body

**Surface Treatment:** 

Passivate hub

**Surface Treatment Specification:** 

Mil-f-14072, finish e300 military specification single treatment response hub

## NSN 3020-00-087-9733

Spur Antibacklash Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-7720 spec.