NSN 3020-00-088-5187

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-088-5187 **Outside Diameter:** 3.500 inches **Overall Length:** 0.937 inches **Keyway Width:** 0.126 inches **Thread Size:** 1/4-20 **Bore Diameter:** 0.500 inches **Bore Length:** 0.937 inches **Distance From Center Of Bore To Bottom Of Keyway:** 0.311 inches Pitch Diameter: 3.198 inches **Securing Hole Quantity:** 2 Face Width: 0.171 inches Guide: Not included **Design Form:** Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** Located on top of keyway and 90 degrees from keyway **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Threaded hole **Lightening Hole:** Not included

Plain **Securing Location:**

Protruding Hub Characteristic:

Aa end

NSN 3020-00-088-5187 Sprocket Wheel - Page 2 of 2



Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
10
Asa Standard Chain Number:
80
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
1.000 inches
Hub End Outside Diameter And Location:
1.625 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.766 inches both ends
Material:
Iron malleable
Quantity:
1
Style Designator:
Plain
Fsc Application Data:
Test stand, hydraulic system components, acft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
Т353-с