NSN 3020-00-089-0436

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-089-0436

Parks Chida
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
2.6560 inches
Teeth Quantity:
170
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
2.6880 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.188 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.188 inches first end
End Diameter:
0.500 inches first end
First Step Length:
0.062 inches first end
First Step Diameter:
0.875 inches first end
Material:

Materia

Aluminum alloy 2024

NSN 3020-00-089-0436

Spur Gear - Page 2 of 2



Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A27300