NSN 3020-00-089-2088

Spur Gear - Page 1 of 2

Body Style:

Webbed, offset, solid **Spline Quantity:**16 both ends

Attachment Method:

Mounting hole

Pitch Diameter:
7.6667 inches

Teeth Quantity:

46



View Online at https://aerobasegroup.com/nsn/3020-00-089-2088

Bore Style:	
Involute spline both	ends
Spline Pitch Diame	eter:
2.0000 inches both	ends
Hardness Rating:	
30.0 rockwell c and	d 40.0 rockwell c
Mounting Hole Typ	e And Quantity:
3 plain transversely	through face
Outside Diameter:	
8.0070 inches	
Tooth Form:	
Standard	
Pressure Angle:	
25.0000 degrees	
Distance Between	Body Face And Protruding Hub End:
0.4450 inches first e	end
Face Width:	
1.120 inches	
Bore Diameter:	
2.1250 inches both	ends
Hub Style Designat	tor:
Plain both ends	
Hub Diameter:	
2.6500 inches both	ends
Mounting Hole Dia	meter:
0.750 inches axially	through body, first end
Bolt Hole Circle Dia	ameter:
4.500 inches axially	through body, first end
Material:	
Steel comp 5140	
Material Specificati	ion:
- 1	si/sae 5140 federal standard single material response

NSN 3020-00-089-2088

Spur Gear - Page 2 of 2



Sty	عا	D	26	ia	n	a	ŧ٥	r	•
JLY	ı	יש	ငၥ	щ		а	ιv	ш	

One protruding hub, one flush hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300