## NSN 3020-00-092-3801

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-092-3801

| Outside Diameter:                        |
|--|
| 0.842 inches                             |
| Overall Length:                          |
| 0.500 inches                             |
| Thread Size:                             |
| 0.125-40                                 |
| Bore Diameter:                           |
| 0.250 inches                             |
| Bore Length:                             |
| 0.500 inches                             |
| Pitch Diameter:                          |
| 0.816 inches                             |
| Securing Hole Quantity:                  |
| 1  |
| Face Width:                              |
| 0.187 inches                             |
| Design Form:                             |
| Plain                                    |
| Bore Type:                               |
| Straight                                 |
| Counterbore Feature:                     |
| Not included                             |
| Hole Location:                           |
| On hub                                   |
| Keying Facility:                         |
| Not included                             |
| Securing Method:                         |
| Threaded hole                            |
| Lightening Hole:                         |
| Not included                             |
| Protruding Hub Characteristic:           |
| Plain                                    |
| Securing Location:                       |
| Aa end                                   |
| Belt/chain/film Size For Which Designed: |
| Ladder chain                             |
| Teeth Row Quantity:                      |
| 1  |
| Teeth Quantity Per Row:                  |
| 24                                       |
| Hardness Rating Test Method:             |

Not rated

## **NSN 3020-00-092-3801** Sprocket Wheel - Page 2 of 2



| Bore Bearing:  |  |
|--|--|
| Not included   |  |
| Hub External Keyway:   |  |
| Not included   |  |
| Tooth Pitch:   |  |
| 0.106 inches   |  |
| Hub End Outside Diameter And Location:   |  |
| 0.375 inches aa end  |  |
| Distance From Outside Flange/rim To Hub End And Location:                          |  |
| 0.313 inches aa end  |  |
| Material:  |  |
| Steel, qq-s-764, type 303, cond a-canceled   |  |
| Material:  |  |
| Steel comp 303   |  |
| Material Specification:  |  |
| Qq-s-764, type 303, cond a-canceled federal specification single material response |  |
| Surface Treatment:   |  |
| Passivate  |  |
| Style Designator:  |  |
| Webbed or spoked   |  |
| Surface Treatment:   |  |
| Passivated   |  |
| Shelf Life:  |  |
| N/a  |  |
| Unit Of Measure:   |  |
| -  |  |
| Demilitarization:  |  |
| No   |  |
| Filg:  |  |
| Г353-с   |  |
|  |  |