NSN 3020-00-097-8256

Groove Pulley - Page 1 of 2

Counterbore Diameter:

Counterbore Depth:

1.600 inches

0.511 inches **Groove Depth:**0.625 inches **Groove Width:**



View Online at https://aerobasegroup.com/nsn/3020-00-097-8256

| 0.562 inches |
|--|
| Outside Diameter: |
| 4.875 inches |
| Overall Length: |
| 1.685 inches |
| Thread Size: |
| 0.250-20 |
| Bore Diameter: |
| 1.550 inches |
| Bore Length: |
| 1.566 inches |
| V Groove Angle In Deg: |
| 30.0 |
| Pitch Diameter: |
| 4.625 inches |
| Securing Hole Quantity: |
| 4 |
| Material And Location: |
| Steel |
| Face Width: |
| 1.625 inches |
| Design Form: |
| Webbed |
| Bore Type: |
| Straight |
| Bearings: |
| Not included |
| Groove Quantity: |
| 2 |
| Counterbore Feature: |
| Included |
| Counterbore Location: |
| Bb end |
| Hole Location: |
| Equally spaced on 2.500 in. Diameter bolt circle |
| |
| |
| |

NSN 3020-00-097-8256 Groove Pulley - Page 2 of 2



| Keying Facility: |
|---|
| Not included |
| Securing Method: |
| Threaded hole |
| Split Hub Feature: |
| Not included |
| Web/spoke Relationship To Face Centerline: |
| Not offset |
| Lightening Hole: |
| Not included |
| Integral Cooling Vane: |
| Not included |
| Groove Shape: |
| V |
| Bore Feature: |
| Included |
| Protruding Hub Characteristic: |
| Plain |
| Securing Location: |
| Aa end |
| Hub End Outside Diameter And Location: |
| 3.000 inches aa end |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.060 inches aa end and 0.119 inches bb end |
| Surface Treatment: |
| Tinners red |
| Style Designator: |
| Webbed or spoked |
| Surface Treatment: |
| Tinners red |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T353-a |