NSN 3020-00-100-4744



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-100-4744 **Body Style:** Webbed, offset, solid **Attachment Method:** Mounting hole Pitch Diameter: 2.1666 inches **Teeth Quantity:** 104 **Bore Style:** W/counterbore first end **Mounting Hole Thread Series Designator:** Unc axially through body, second end and unf axially through body, second end **Mounting Hole Thread Size:** 0.065 inches axially through body, second end and 0.067 inches axially through body, second end **Mounting Hole Type And Quantity:** 8 threaded axially through body, second end **Outside Diameter:** 2.207 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.040 inches second end **Face Width:** 0.064 inches **Bore Diameter:** 0.250 inches both ends **Counterbore Depth:** 0.028 inches first end **Counterbore Diameter:** 0.315 inches first end **Hub Style Designator:** Plain both ends **Hub Diameter:** 2.110 inches first end **Precision Classification:**

Precision Classification
Quality number 8
Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6 federal specification single material response

NSN 3020-00-100-4744

Spur Gear - Page 2 of 2

Mil-a-8625 spec.



Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):