## NSN 3020-00-102-3755

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-102-3755

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.8750 inches
Teeth Quantity:
42
Bore Style:
W/counterbore both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thread Size:
0.0860 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded axially through body, first end
Outside Diameter:
0.9145 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.187 inches first end
Face Width:
0.094 inches
Bore Diameter:
0.125 inches both ends
Counterbore Depth:
0.046 inches second end
Counterbore Diameter:
0.500 inches second end
Hub Style Designator:
Plain first end
Hub Diameter:
0.312 inches first end
Precision Classification:
Quality number 10
Material:

Steel

## **NSN 3020-00-102-3755** Spur Gear - Page 2 of 2

Fiig: A27300



Material Specification:
Qq-s-764, type 303 federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No