## NSN 3020-00-102-3756



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-102-3756 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.5615 inches and 0.5625 inches **Teeth Quantity:** 27 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.603 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.218 inches first end **Face Width:** 0.094 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 303 **Material Specification:** Qq-s-764, type 303, cond a federal specification single material response

**Surface Treatment:** 

**Passivate** 

## NSN 3020-00-102-3756

Spur Gear - Page 2 of 2



Sty	16	u	=5	ıu	 aı	u	ч.	_

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300