## NSN 3020-00-102-4126

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-102-4126 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.8323 inches and 0.8333 inches **Teeth Quantity:** 40 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.874 inches Nominallength: 0.325 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.200 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.187 inches both ends **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material: Aluminum alloy 6061 **Material Specification:** Qq-a-225/8, t6 federal specification single material response **Surface Treatment:** Anodize **Style Designator:** Protruding hub

N/a

Shelf Life:

## **NSN 3020-00-102-4126** Spur Gear - Page 2 of 2



			ıre:

Demilitarization:

No

Fiig:

A27300