## NSN 3020-00-102-6254

Flat Pulley - Page 1 of 2



| , ,   | dioup |
|---|-------|
| View Online at https://aerobasegroup.com/nsn/3020-00-102-6254 |       |
| Outside Diameter:   |       |
| Between 0.999 inches and 1.000 inches                         |       |
| Thread Size:  |       |
| 0.112-40  |       |
| Bore Diameter:  |       |
| 0.187 inches  |       |
| Bore Length:  |       |
| 0.220 inches  |       |
| Securing Hole Quantity:                                       |       |
| 2   |       |
| Material And Location:  |       |
| Steel, ams 5643, condition a                                  |       |
| Face Width:   |       |
| 0.220 inches  |       |
| Design Form:  |       |
| Plain   |       |
| Bore Type:  |       |
| Straight  |       |
| Bearings:   |       |
| Not included  |       |
| Counterbore Feature:  |       |
| Not included  |       |
| Hole Location:  |       |
| Holes 100 degrees apart                                       |       |
| Keying Facility:  |       |
| Not included  |       |
| Securing Method:  |       |
| Threaded hole   |       |
| Split Hub Feature:  |       |
| Not included  |       |
| Lightening Hole:  |       |
| Not included  |       |
| Integral Cooling Vane:  |       |
| Not included  |       |
| Crown Face:   |       |

Solid

**Bore Feature:** 

Not included Rim Type:

Included

**Securing Location:** 

Pulley surface

## NSN 3020-00-102-6254

Flat Pulley - Page 2 of 2



| Surface Treatment: |
|--------------------|
| Passivate          |
| Style Designator:  |
| Plain              |
| Surface Treatment: |
| Passivated         |
| Shelf Life:        |
| N/a                |
| Unit Of Measure:   |
|                    |
| Demilitarization:  |
| No                 |

**Fiig:** T353-a