## NSN 3020-00-103-0858

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-103-0858

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 10.8149 inches **Teeth Quantity:** 61 **Bore Style:** W/counterbore both ends Hardness Rating: 30.0 rockwell c and 40.0 rockwell c Mounting Hole Type And Quantity: 1 plain transversely through hub, first end **Outside Diameter:** 5.802 inches Nominallength: 0.2700 inches **Tooth Form:** Standard **Pressure Angle:** 22.5000 degrees Distance Between Body Face And Protruding Hub End: 0.020 inches both ends Face Width: 0.2300 inches **Bore Diameter:** 5.063 inches both ends **Counterbore Depth:** 0.064 inches both ends **Counterbore Diameter:** 5.130 inches both ends Hub Style Designator: Plain both ends **Hub Diameter:** 5.430 inches both ends Mounting Hole Diameter: 0.067 inches transversely through hub, first end Material: Steel uns k24065 **Material Specification:** 

Ams 6470 assn standard single material response

# NSN 3020-00-103-0858

Spur Gear - Page 2 of 2



Surface Treatment:

Silver body

### Surface Treatment Specification:

Ams2410 assn standard single treatment response body or ams2412 assn standard single treatment response body

#### Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A27300