## NSN 3020-00-103-1406

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-103-1406 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.6667 inches **Teeth Quantity:** 20 **Bore Style:** D both ends Hardness Rating: 30.0 rockwell c and 35.0 rockwell c **Criticality Code Justification:** Feat **Mounting Hole Type And Quantity:** 2 plain transversely through hub, first end **Outside Diameter:** 1.830 inches Nominallength: 0.720 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.325 inches first end **Face Width:** 0.310 inches **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.940 inches first end **Precision Classification:** Quality number 9 **Mounting Hole Diameter:** 0.189 inches transversely through hub, first end **Special Features:** Flight safety critical

Material:

Steel comp 4140

## **Material Specification:**

Qq-s-624 federal specification single material response

## NSN 3020-00-103-1406

Spur Gear - Page 2 of 2



_	•		_	-		
<b>ن</b>	ırfa	$\sim$	I rc	nter	nor	٠.

Passivate

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A27300