NSN 3020-00-104-2772

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-104-2772

| Body Style: Webbed, offset, solid Attachment Method: Clamp Pitch Diameter: 0.6500 inches Teeth Quantity: 52 Bore Style: Plain both ends |
|--|
| Attachment Method: Clamp Pitch Diameter: 0.6500 inches Teeth Quantity: 52 Bore Style: |
| Clamp Pitch Diameter: 0.6500 inches Teeth Quantity: 52 Bore Style: |
| Pitch Diameter: 0.6500 inches Teeth Quantity: 52 Bore Style: |
| 0.6500 inches Teeth Quantity: 52 Bore Style: |
| Teeth Quantity: 52 Bore Style: |
| 52 Bore Style: |
| Bore Style: |
| - |
| Plain both ends |
| |
| Outside Diameter: |
| 0.6724 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.160 inches first end |
| Distance Between Body Face And Recessed Hub End: |
| 0.0180 inches second end |
| Face Width: |
| 0.100 inches |
| Bore Diameter: |
| 0.0937 inches both ends |
| Hub Style Designator: |
| Split first end |
| Hub Diameter: |
| 0.1555 inches first end |
| Material: |
| Steel comp 303 hub |
| Material Specification: |
| Qq-s-764 cond a-cancelled federal specification single material response hub |
| Surface Treatment: |
| Passivate hub |
| Style Designator: |
| One protruding hub, one recessed hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 3020-00-104-2772 Spur Gear - Page 2 of 2



Fiig:

A27300