## NSN 3020-00-104-4980

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-104-4980 **Attachment Method:** Clamp Pitch Diameter: 0.9271 inches **Teeth Quantity:** 89 **Bore Style:** Plain both ends **Outside Diameter:** 0.947 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.205 inches first end **Face Width:** 0.095 inches **Bore Diameter:** 0.090 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.188 inches first end **Clamping Surface Length:** 0.186 inches first end Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** se

Carrage Treatment openioanem
Mil-a-8625, type 1 military specification single treatment respons
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 3020-00-104-4980

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.