## NSN 3020-00-104-9288

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-104-9288

Attachment Method:
Mounting hole
Teeth Quantity:
219
Bore Style:
Plain both ends
Pitch Radius:
1.8245 inches
Mounting Hole Thread Series Designator:
Unc axially through hub, first end
Mounting Hole Thread Size:
0.112 inches axially through hub, first end
Mounting Hole Type And Quantity:
1 threaded axially through hub, first end
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.2780 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.188 inches both ends
Hub Style Designator:
1 step first end
Outside Radius:
0.920 inches
End Length:
0.030 inches first end
End Diameter:
0.256 inches first end
First Step Length:
0.248 inches first end
First Step Diameter:
0.375 inches first end
Arc Length:
0.120 inches
Special Features:
0.600 in.Dia hole in gear face, 0.550 in.From bore center to hole center
Material:
Steel comp 303s

## NSN 3020-00-104-9288

Spur Gear Sector - Page 2 of 2



Material Specification:

Mil-s-7720 cond a military specification single material response

## Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** No

\_\_\_\_

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.