

View Online at <https://aerobasegroup.com/nsn/3020-00-106-4046>

Groove Depth:

Between 0.310 inches and 0.315 inches

Groove Width:

Between 0.955 inches and 0.980 inches

Outside Diameter:

Between 2.078 inches and 2.083 inches

Bore Diameter:

Between 0.5025 inches and 0.5035 inches

Bore Length:

Between 1.005 inches and 1.010 inches

Groove Radius:

Between 0.500 inches and 0.505 inches

Material And Location:

Cres ams5630 comp 440c o/a

Face Width:

Between 1.005 inches and 1.010 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Keying Facility:

Not included

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

U

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Hub End Outside Diameter And Location:

0.900 inches both ends

Criticality Code Justification:

Abxv

Surface Treatment:

Passivated mp5205 type 3 fscm 05151bxsm dpd

Style Designator:

Webbed or spoked

Surface Treatment:

Passivated mp5205 type 3 fscm 05151bxsm dpd

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T353-a