NSN 3020-00-106-4052

Sprocket Wheel - Page 1 of 2

Spline Major Diameter:

0.843 inches



View Online at https://aerobasegroup.com/nsn/3020-00-106-4052

Outside Diameter:
Between 1.731 inches and 1.761 inches
Overall Length:
0.600 inches
Spline Quantity:
26
Spline Minor Diameter:
0.781 inches
Pitch Diameter:
1.567 inches
Face Width:
Between 0.160 inches and 0.168 inches
Design Form:
Plain
Bore Type:
Involute spline
Metallic Hardness Rating And Location:
40.0 rockwell c body and 45.0 rockwell c body
Spline Pressure Angle In Deg:
30.0
Spline Length:
0.600 inches
Counterbore Feature:
Not included
Spline Pitch Diameter:
0.8125 inches
Securing Method:
Any acceptable
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Securing Location:
Aa end or bb end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:

NSN 3020-00-106-4052 Sprocket Wheel - Page 2 of 2



Teeth Quantity Per Row:
13
Asa Standard Chain Number:
35
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 40.0 rockwell c and 45.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.375 inches
Hub End Outside Diameter And Location:
1.100 inches aa end and 1.100 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
0.227 inches aa end and 0.223 inches bb end
Material:
Steel
Material:
Steel
Surface Treatment:
Oxide
Style Designator:
Plain
Surface Treatment:
Black oxide
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c