

View Online at <https://aerobasegroup.com/nsn/3020-00-106-4437>

Groove Depth:

Between 0.612 inches and 0.625 inches

Groove Width:

0.625 inches

Outside Diameter:

6.750 inches

Overall Length:

1.000 inches

Keyway Width:

0.250 inches

Bore Diameter:

1.000 inches

Bore Length:

1.000 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.619 inches and 0.629 inches

V Groove Angle In Deg:

34.0

Pitch Diameter:

Between 6.000 inches and 6.400 inches

Furnished Items And Quantity:

Taper-lock bushing one each; capscrew two each

Material And Location:

Iron, cast

Face Width:

0.875 inches

Design Form:

Spoked

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Tapered-lock bushing

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

A and b

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Hub End Outside Diameter And Location:

3.000 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.125 inches aa end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T353-a