NSN 3020-00-108-1634



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-108-1634 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.6243 inches and 0.6250 inches **Teeth Quantity:** 60 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 56 axially through body, first end **Mounting Hole Thread Size:** 0.086 inches axially through body, first end **Mounting Hole Type And Quantity:** 3 threaded axially through body, first end **Outside Diameter:** 0.645 inches Nominallength: 0.182 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.090 inches first end **Face Width:** 0.092 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.250 inches first end **Precision Classification:** Quality number 12 **Bolt Hole Circle Diameter:**

0.406 inches axially through body, first end

Mtg holes spaced 120 degrees apart

Special Features:

NSN 3020-00-108-1634

Spur Gear - Page 2 of 2

Fiig: A27300



Material:
Steel comp 303
Material Specification:
$\ensuremath{Qq}\text{-s-764},$ type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No