NSN 3020-00-109-9592

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-109-9592

Attachment Method:
Mounting hole
Pitch Diameter:
0.7833 inches
Teeth Quantity:
94
Mounting Hole Type And Quantity:
1 plain axially through body, first end
Outside Diameter:
0.800 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.188 inches first end
Face Width:
0.151 inches
Hub Style Designator:
2 steps first end
End Length:
0.063 inches second end
End Diameter:
0.093 inches both ends
First Step Length:
0.056 inches first end
First Step Diameter:
0.125 inches both ends
Second Step Length:
0.040 inches first end
Second Step Diameter:
0.187 inches first end
Mounting Hole Diameter:
0.031 inches axially through body, first end
Material:
Steel comp 303
Material Specification:
Mil-s-7720, cond a military specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:

Mil-std-171, finish no.5.4.1 military standard single treatment response

NSN 3020-00-109-9592

Spur Antibacklash Gear - Page 2 of 2



Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-7720 spec.