

View Online at <https://aerobasegroup.com/nsn/3020-00-110-5188>

Groove Depth:

0.490 inches

Groove Width:

0.490 inches

Outside Diameter:

6.000 inches

Overall Length:

1.250 inches

Keyway Width:

0.250 inches

Thread Size:

0.312-18

Bore Diameter:

1.000 inches

Bore Length:

1.031 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.625 inches

V Groove Angle In Deg:

38.0

Pitch Diameter:

Between 5.500 inches and 5.900 inches

Securing Hole Quantity:

1

Furnished Items And Quantity:

Setscrew, one each

Material And Location:

Iron, cast

Face Width:

0.750 inches

Design Form:

Spoked

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Hole Location:

Centered 0.312 in. From end of hub top of keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

3I and 4I

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Hub End Outside Diameter And Location:

1.812 inches aa end and 2.000 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

0.375 inches aa end and 0.219 inches bb end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a