NSN 3020-00-110-6925

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-110-6925 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.6666 inches **Teeth Quantity:** 80 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.0860 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.6830 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.135 inches first end **Face Width:** 0.040 inches **Bore Diameter:** 0.094 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.320 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 303 **Material Specification:**

Mil-s-7720, comp 303s military specification single material response

Surface Treatment:

Passivate

NSN 3020-00-110-6925

Spur Gear - Page 2 of 2



Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Mil-s-7720 spec.

Mil-std (military Standard):

Fiig: A27300