NSN 3020-00-110-6925

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-110-6925

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.6666 inches **Teeth Quantity:** 80 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.0860 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 threaded transversely through hub, first end **Outside Diameter:** 0.6830 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.135 inches first end Face Width: 0.040 inches **Bore Diameter:** 0.094 inches both ends Hub Style Designator: Plain first end **Hub Diameter:** 0.320 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 303 **Material Specification:** Mil-s-7720, comp 303s military specification single material response **Surface Treatment:** Passivate

NSN 3020-00-110-6925

Spur Gear - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.