NSN 3020-00-112-0062



Spur Antibacklash Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-112-0062 **Attachment Method:** Mounting hole Pitch Diameter: 2.5000 inches **Teeth Quantity:** 180 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 2.526 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.562 inches first end **Special Features:** Attaching holes spaced 90 degrees apart through hub Material: Steel comp 303 hub **Material Specification:** Qq-s-763, class 303, cond a federal specification single material response hub **Surface Treatment:** Passivate hub **Style Designator:**

Protruding hub

NSN 3020-00-112-0062

Spur Antibacklash Gear - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300