NSN 3020-00-113-3320

1 retaining ring

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-113-3320

| Attachment Method: |
|---|
| Clamp |
| Pitch Diameter: |
| 1.3333 inches |
| Teeth Quantity: |
| 128 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade c |
| Outside Diameter: |
| 1.352 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.302 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.188 inches both ends |
| Hub Style Designator: |
| Split first end |
| Hub Diameter: |
| 0.248 inches first end |
| Clamping Surface Length: |
| 0.271 inches first end |
| Precision Classification: |
| Quality number 12 |
| Special Features: |
| Furnished items; spring retaining balls 4; compression springs 2; and shim and washer as required |
| Material: |
| Aluminum alloy 2024 |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 1 military specification single treatment response |
| Style Designator: |
| Protruding hub |
| Furnished Items And Quantity: |

NSN 3020-00-113-3320

Spur Antibacklash Gear - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A27300 | |

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: