NSN 3020-00-113-9161



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-113-9161 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.2166 inches **Teeth Quantity:** 26 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.0860 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.2330 inches **Tooth Form:** Standard Flange Diameter: 0.320 inches **Pressure Angle:** 20.0000 degrees Flange Thickness: 0.146 inches **Face Width:** 0.050 inches **Bore Diameter:** 0.094 inches both ends **Distance Between Outer Body Face And Inner Flange Face:** 0.1340 inches **Hub Style Designator:** Plain first end **Hub Diameter:** 0.1800 inches between body and flange **Precision Classification:**

Quality number 10 Material:

Steel comp 303

NSN 3020-00-113-9161

Spur Gear - Page 2 of 2



Material Specification: Mil-s-7720, comp 303s military specification single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Style Designator: Flanged end Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fiig:

Mil-s-7720 spec.

Mil-std (military Standard):

A27300