NSN 3020-00-116-4250

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-116-4250

Attachment Method: Mounting hole **Serration Quantity:** 36 both ends **Teeth Quantity:** 52 **Bore Style:** Serrated both ends **Serration Pitch Diameter:** 0.5000 inches both ends **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.150 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end Nominallength: 0.250 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.0940 inches first end **Face Width:** 0.624 inches **Hub Style Designator:** Plain first end **Hub Diameter:** 0.1560 inches first end **Outside Radius:** 0.842 inches Arc Length: 0.8440 inches

Material:

Aluminum

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Anodize

NSN 3020-00-116-4250

Spur Gear Sector - Page 2 of 2



Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.