NSN 3020-00-118-3541

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-118-3541

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.1667 inches
Teeth Quantity:
7
Bore Style:
W/counterbore counterbore, first end
Mounting Hole Thread Series Designator:
Unf axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
24 axially through hub, first end
Hardness Rating:
30.0 rockwell c and 40.0 rockwell c
Mounting Hole Thread Size:
0.375 inches axially through hub, first end
Mounting Hole Type And Quantity:
1 threaded axially through hub, first end
Outside Diameter:
1.500 inches
Nominallength:
4.312 inches
Tooth Form:
Standard
Pressure Angle:
28.0000 degrees
Distance Between Body Face And Protruding Hub End:
1.277 inches first end
Face Width:
2.124 inches
Bore Diameter:
0.125 inches counterbore, first end
Counterbore Depth:
3.148 inches counterbore, first end
Counterbore Diameter:
0.334 inches counterbore, first end
Hub Style Designator:
Plain second end
Hub Diameter:

0.602 inches second end

NSN 3020-00-118-3541 Spur Gear - Page 2 of 2

Fiig: A27300



Special Features:
Externally splined hub first end, 0.6563 in.Spline pitch dia, 21 splines
Material:
Steel comp e9310
Material Specification:
6260 assn standard single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No